



INT 30M

Manual-feed horizontal end-milling machine. Cutter unit pneumatic quick change. Performs milling operations, also off size between -45° and $+45^{\circ}$. Fully protected work area. Scratchproof worktop. Forward movement on ball-bearing guides and runners ensures smooth and precise operation over the years. Self-braking motor and horizontal and vertical pneumatic clamps with low-pressure device making the machine particularly safe for the operator.

Revolver depth stop with 6 adjustable positions and micro-mist pneumatic tool lubrication (emulsified oil) speed up the work cycle. The integrated mill cutter magazine and conveyed shaving ejection make the machine tidy and clean.

Technical details

| | | |
|-----------------------------|-----------------|---------|
| Three-phase power supply | 380/400 - 50/60 | Volt-Hz |
| Three-phase motor | 1.1 | kW |
| Spindle | 2850 | rpm. |
| X axis stroke | 300 | mm |
| Clamp capacity | 200 x 120 | mm |
| Max cutter diameter | 160 | mm |
| Milling angle ("F" version) | -45...+45 | ° |
| Weight | 120 | kg |

Fittings

Service spanner bag
 Operator's and maintenance manual with EC declaration
 Ø 27/32 L=135 mm cutter holders
 Pin for retaining cutters on holders
 Adjustable levelling feet
 Air blowing gun for cleaning

Accessories

Profile support roller conveyor L=150 mm
 Cutter units to specification