



## **TMA 60A**

Cutting off machine with ascending large cutting capacity with automatic blade advancement. Vertical fence adjustable in two positions to increase the capacity of cutting; cutting angle of up to 15 ° right and left with three fixed positions - 45 °, 0 °, + 45 ° for quick placement. Cutting area guard. Worktop ground steel upward movement head on guides and roller ball process ensures rigidity and precision. Vertical pneumatic clamps with low pressure device and work area guard put the car at the highest levels of safety. Adjust speed hydropneumatic feed. Chip collection drawer and preparation for attack aspotazione fumes make the machine clean and tidy. Blade lubrication pneumatic mist (emulsified oil).

## Technical datas

Power supplies treephase	380/400 - 50/60	Volt-Hz
Power motor treephase	5.5	kW
Speed rotating blade	2850	r.p.m.
Diameter blade	600	mm
2 Positions vertical fence	0/120	mm
Tilt adjustable blade	-15...+15	°
Weight	500	kg

## Standard equipement

Service spanners  
Use and maintenance manual and ce marking  
Blade with carbide teeth HM Ø600 mm (installed)  
Adjustable leveling feets (installed)  
Air gun for cleaning (installed)

## Options

Tool lubrification pulse (neat oil)  
Loading roller: RIS 22-44-66  
Unloading roller: RIS 20M-40M-17V-40V-60V-40E-60E  
Industrial vacuum wheeled model ASP 15